

We manufacture two principal configurations for our non-heated suction tables:



With integrated (built in) suction unit

- Suction unit, Readout and *Carbon Filter permanently mounted on support frame
- Easy to move on lockable castors
- Everything in one package
- Accepts all options and accessories

** Not shown*

Uses:

- Distortion removal and restraint during drying of paper, parchment and textiles
- Dimensional re-adjustment
- Repair application
- Consolidation



With independent, mobile suction unit

- Suction Unit and Carbon Filter separable from table for independent use.
- Suction unit withdraws to allow ample leg room for seated users
- Accepts all options and accessories

- Consolidation
- Spot cleaning
- Adhesive residue removal
- Small area suction flow washing
- Pulp filling
- Impregnation

Features

- High grade aluminium perforated work top, hand finished for flatness
- All round non-perforated edge for effective masking of object
- Sturdy, welded steel support frame with fully lockable castors
- Direct drive suction units providing precisely controllable, powerful suction
- Hand held speed control dial which can be positioned right next to the object
- A full range of optional, purpose-made accessories

Sizes

All dimensions relate to the perforated work surface, please add approximately 30mm to all four sides to allow for the non-perforated edge of the table.

- A1 (594 mm x 841 mm) • A0 (841 mm x 1189 mm) • 2A0 (1682 mm x 1189 mm)
- 6 feet x 4 feet (1800mm x 1200mm) slightly longer than the 2A0

Options and Accessories



Left to right: Removable acrylic hood, four leg height adjustment (factory fitted only), Standard Moisture Trap, In-line Carbon Filter. Other accessories available: Humidification Package, High Volume Moisture Trap, Acrylic Dome.

Integrated suction units can be fitted with a divert valve to facilitate use with other suction equipment. For large scale washing treatments we recommend our Textile Suction Washing Table.

If you require a heated table, please see details of our Multi-Function Suction Tables.

Specifications

Rated Voltage	230 VAC (or 115VAC)
Rated Power	16Amp (or 32amp)
Rated Frequency	50 Hz (60Hz)

Other Willard Conservation Products

- Multi-Function Heated Painting and Textile Suction Tables
- Textile Suction Cleaning Table
- Miniature-Suction Platform •
- Suction Platens
- Book Wedge
- Heated Spatulas
- Lab Sinks
- Lighting...and more.